2.5 TONNE SWIVEL

SPECIFICATION

All dimensions below were correct at time of print, E&OE.



Equipped with a 180° slewing skip, the C30R-3 allows the operator to side tip from both forward tipping and rear tipping configuration. The engine complies with Tier 4i emissions/EU Stage 111B.

A Bi-Directional seat system that dramatically reduces the amount of turning and reversing, making this machine is a great choice for projects of any size with restricted space.

MODEL: C30R-3

4 CYLINDER, DISPLACEMENT: 2.2 LITRES

46.6PS / 34.3KW @ 2800RPM / Stage IIIB

FUEL TANK CAPACITY: 58 LITRES

BI-DIRECTIONAL SEAT POSITIONS

MACHINE WEIGHT: 2650KG • PAYLOAD: 2500KG

MAX TRAVEL SPEED: 11KPH

GRADEABILITY (EMPTY): 30°

GROUND PRESSURE (UNLOADED): 0.30KG/CM²

GROUND PRESSURE (LOADED): 0.57KG/CM2

TRACK WIDTH: 320MM • SLEW RADIUS: 1600MM

DUMP BODY CAPACITY (STRUCK): 0.88M3


DUMP BODY CAPACITY (HEAPED): 1.24M3












TOTAL HEIGHT: 2310mm



TOTAL LENGTH: 3640mm

FEATURE ICONS



ROPS OPERATORS CAB



BIODEGRADABLE HYDRAULIC OIL



HYDRAULIC ISOLATION SYSTEM



360° CAMERA



360° SLEWING



SEATBELT BEACON SYSTEM



REVERSING CAMERA





